

Amendments to the Claims:

1. (withdrawn) A system for accepting user input, comprising:
a plurality of switches;
a pressure member coupled to the plurality of switches, the pressure member having multiple sections, wherein each section of the multiple sections is associated with a switch of the plurality of switches; and
wherein the pressure member is positioned in relation to the plurality of switches such that when a force is applied by a user to one of the multiple sections, the pressure member transmits a resulting force to a switch associated with the one of the multiple sections thereby causing actuation of the switch associated with the one of the multiple sections.
2. (withdrawn) The system of claim 1 further comprising a display, wherein the display displays at least one input option and wherein at least one of the multiple sections of the pressure member is spatially associated with the at least one input option displayed.
3. (withdrawn) The system of claim 2 wherein at least a portion the pressure member is optically transparent, the pressure member is further positioned in front of the display so that the display is visible through the pressure member, the plurality of switches is further located adjacent to the display and the at least one input option displayed is viewed through the pressure member.
4. (withdrawn) The system of claim 3 wherein the system operates in a motor vehicle.
5. (withdrawn) The system of claim 1 wherein the system operates in a motor vehicle.
6. (withdrawn) The system of claim 1 wherein the system operates as a component of a media player.
7. (withdrawn) The system of claim 1 wherein the at least one of the multiple sections has a tactile element, wherein the tactile element reduces the requirement for a visual location, by the user, of the at least one of the multiple sections of the pressure member.

8. (withdrawn) The system of claim 1 wherein the pressure member includes four sections and wherein each section is associated with one of the four switches.
9. (withdrawn) The system of claim 1 wherein the pressure member transmits a resulting force to a single switch associated with the one of the multiple sections.
10. (withdrawn) The system of claim 1 wherein the pressure member transmits a resulting force to at least two switches associated with the one of the multiple sections.
11. (withdrawn) The system of claim 1 wherein the switch actuation initiates a system operation.
12. (withdrawn) The system of claim 1 wherein the mechanical characteristics of the pressure member are spatially varied, in order to focus forces exerted upon a selected section of the pressure member to effect a desired switch actuation.
13. (withdrawn) The system of claim 1 comprising:
 - a first switch of the plurality of switches;
 - a second switch of the plurality of switches; and
 - a control circuit;wherein, as a result of the exertion of a force by the user to the pressure member, the pressure member transmits a first resulting force to a first switch associated with one of the multiple sections of the pressure member and a second resulting force to a second switch associated with another of the multiple sections of the pressure member thereby causing an actuation of the first switch of the plurality of switches and an actuation of the second switch of the plurality of switches;
whereupon the control circuit identifies a multiple switch activation as an inferred system state.

14. (withdrawn) The system of claim 1, further comprising a fulcrum that localizes deflection of the pressure member resulting from forces applied by a user, in order to affect which switches are actuated by the applied force.
15. (withdrawn) The system of claim 1 wherein the system, in response to the exertion of a force on the pressure member by the user, provides confirmation of a user input to the user.
16. (withdrawn) The system of claim 1, further comprising an indicator light, wherein the indicator light upon the exertion of a force to the pressure member by a user, is configured to illuminate in order to provide a visual confirmation of the switch actuation to the user.
17. (withdrawn) The system of claim 1 wherein the system is configured to provide an audible confirmation of the switch actuation to the user.
18. (withdrawn) The system of claim 17 wherein the audible confirmation of the switch actuation is a synthetic voice.
19. (currently amended) A system for accepting user input, comprising:
 - a first control configured to select a media source in response to an actuation of the first control by a user;
 - a second control; that is different from the first control and ~~wherein the second control~~ has two degrees of freedom, ~~in actuation~~ the second control configured to choose a mode from a set of modes for the selected media source in response to an actuation of the first degree of freedom of the second control by the user, wherein actuation of the second degree of freedom by the user ~~of the second control is configured to identify~~ identifies a media content item selection; and
 - a display for displaying one of the media source, the mode and the media content item.

20. (original) The system for accepting user input of claim 19, further comprising a pressure member coupled to a plurality of switches, the pressure member having multiple sections, wherein each section of the multiple sections is associated with a switch of the plurality of switches and wherein the pressure member is positioned in relation to the plurality of switches such that when a force is applied by a user to one of the multiple sections, the pressure member transmits a resulting force to a switch associated with the one of the multiple sections thereby causing actuation of the switch associated with the one of the multiple sections.
21. (original) The system of claim 19 wherein a control comprises a shaft, wherein the shaft is mounted within a void of the pressure member and secured by a fastener.
22. (original) The system of claim 19 wherein the system delays, for a predetermined time, before executing one of a user media source selection, mode selection and media content item selection.
23. (original) The system of claim 19 wherein, upon the occurrence of one of a user media source selections, mode selection, and media content item selection, the system provides a sub-menu of options to the user.
24. (original) The system of claim 19 wherein a display is configured to provide a visual confirmation of the media source selected.
25. (original) The system of claim 24 wherein the display displays a color cue based on a media source selected.
26. (original) The system of claim 24 wherein the display provides a position indicator depicting to the user, the relative position of a selected media content item within a browsable list of media content items, wherein the position indicator is displayed in a radial format.
27. (original) The system of claim 19 wherein the display is a touch screen and wherein the touch screen is configured to process a user input.

28. (previously presented) The system of claim 19 wherein at least one of the first and second controls is configured to provide a visual confirmation of a user input.
29. (original) The system of claim 28 wherein the visual confirmation is text.
30. (original) The system of claim 28 wherein the visual confirmation is a graphic.
31. (original) The system of claim 28 wherein the visual confirmation is a color change.
32. (previously presented) The system of claim 28 wherein at least a portion of the at least one of the first and second controls is optically transparent, wherein the at least one of the first and second controls is positioned over the display and wherein information displayed by the display is visible through the at least one of the first and second controls.
33. (original) The system of claim 32 wherein the visual information is text.
34. (original) The system of claim 32 wherein the visual information is a graphic.
35. (original) The system of claim 32 wherein the visual information is a color change.
36. (original) The system of claim 19 wherein the system is configured to provide an audible confirmation of the media source selected.
37. (original) The system of claim 36 wherein the audible confirmation of the media source selected is a synthetic voice.
38. (original) The system of claim 19 wherein a second control is positioned in front of the display and wherein the second control accepts actuation of the second degree of freedom by the user, as a user input.
39. (currently amended) A system for accepting user input, comprising:
 - (a) at least one switch;
 - (b) a display, wherein the display depicts menu options including:
media ~~content information~~ options; and
control options, wherein the control options are displayed on the display near the switch;

(c) a pressure member disposed over the display, the pressure member being configured to accept a force exerted by a user within a section of the pressure member;

the pressure member further coupled to the at least one switch such that a resulting force transmitted by the pressure member in response to a user applied force causes a switch actuation; ~~and~~

(d) at least one a first control, which has two degrees of freedom in actuation, the at least one control being able to select one of the menu options, configured to make a selection based on the media options, at least a portion of the at least one first control being optically transparent[[.]];and

(e) a second control that is different from the first control and has two degrees of freedom, the second control configured to choose a mode from a set of modes associated with the selection based on the media options in response to an actuation of the first degree of freedom of the second control by the user, wherein actuation of the second degree of freedom by the user identifies a media content item selection.

40. (currently amended) The system of claim 39, wherein the ~~at least one~~ first control is positioned over the display and wherein information displayed by the display is visible through the ~~at least one first~~ control.
41. (original) The system of claim 39 wherein the display displays a color to provide user feedback.
42. (currently amended) The system of claim 40 wherein the ~~at least one first~~ control displays a color to provide user feedback.
43. (currently amended) The system of claim 40 wherein the ~~at least one~~ first control displays ~~[[an]]~~ a symbolic representation of a selected one of the ~~media content source options~~, mode and media content item.
44. (currently amended) The system of claim ~~19~~ 39 ~~for accepting user input, wherein said first control has two degrees of freedom in actuation, and wherein actuation of the first a~~

degree of freedom of the first control is associated with ~~selection of a media source, and the second degree of freedom is associated with~~ control of system volume.

45. (currently amended) A The system of claim 39 ~~system for accepting user input in a media player, comprising wherein~~[[:]]

[[a]] the display is also configured to display ~~for displaying~~ one of the media ~~source~~options, mode and media content item[[;]]

~~at least one control, wherein the at least one control has two degrees of freedom in actuation, wherein the at least one control is disposed over the display and at least a portion of the control is optically transparent such that at least a portion of the display is visible through the at least one control.~~

46. (currently amended) A media player for use in a motor vehicle, comprising:

a plurality of switches;

a display for displaying one of the a media source, a mode and a media content item;

a pressure member coupled to at least one of the plurality of switches, the pressure member disposed over the display wherein at least a portion of the display is visible through the pressure member, the pressure member being configured to accept a force exerted by a user within a section of the pressure member;

a first control configured to select [[a]]the media source in response to an actuation of the first control by a user; and

a second control; that is different from the first control and wherein the second control has two degrees of freedom in actuation, the second control configured to choose [[a]]the mode from a set of modes for the selected media source in response to an actuation of the first degree of freedom of the second control by the user, wherein actuation of the second degree of freedom by the user ~~of the second control is configured to identify~~ identifies [[a]]the media content item selection.

47. (withdrawn) In a system for accepting a user input, a method for accepting the user input, comprising the steps of:
- displaying a set of options on a display to prompt for a user selection, wherein at least a portion of the display is visible through a pressure member, the pressure member being positioned in front of the display;
- generating a switch actuation in response to a force exerted by the user on a section of the pressure member wherein the section of the pressure member corresponds to a desired option, wherein the switch is arranged in an array of switches adjacent to the display; and
- based on the switch actuation, changing a system state.
48. (withdrawn) The method of claim 47, further comprising the step of providing a confirmation in response to the exertion of the force to the section of the pressure member by the user.
49. (withdrawn) The method of claim 48 wherein the confirmation is an audible confirmation.
50. (withdrawn) The method of claim 47, further comprising the step of:
- based on the system state, initiating a system operation.
51. (withdrawn) The method of claim 47 wherein the step of generating a switch actuation comprises the steps of:
- detecting a first switch actuation and a second switch actuation caused by the transmission of a resulting force by the pressure member to the first switch and the second switch; and
- generating an inferred system state.
52. (withdrawn) The method of claim 51 wherein the inferred system state initiates a browse function.
53. (withdrawn) The method of claim 47, further comprising the step of:

accepting actuation of the first degree of freedom of a first control to select one of the following sources: uIndex, AM, FM, satellite radio, compact disk, hard drive, uMusic, DVD, HVAC/climate, core navigation.

54. (withdrawn) The method of claim 47, further comprising the step of:

accepting actuation of the first degree of freedom of a second control to select one of the following modes: AM presets, AM seek, AM tune, FM preset, FM seek, FM tune, FM station, FM song, FM genre, FM artist, satellite radio presets, satellite radio station, satellite radio category, satellite radio station, satellite radio song, satellite radio genre, satellite radio artist, CD Track, CD time, CD Disk, CD Artist, CD Song, CD Genre, hard drive title, hard drive track, hard drive artist, hard drive time, hard drive genre, uMusic track, uMusic time, DVD Chapter, HVAC/climate temperature, HVAC/climate fan, core navigation origin, core navigation destination, core navigation directions.

55. (withdrawn) The method of claim 54, further comprising the steps of:

displaying a list of options pertinent to the selected mode; and

selecting a desired option based on actuation of the first degree of freedom of the second control.